

BAY OIL COMPANY

38 Plainfield Street
Chicopee, Ma. 01013
Tel. 413-737-7728 Fax 413-737-7730

RUST PREVENTIVE 585

What it is RP 585

RP 585 is a solvent cutback, soft wax base, corrosion preventive compound.

Benefits

Easy application

RP 585 is suited for application by either spray, dip or brush.

Low-Cost Protection

RP 585 is a one-coat rust preventive. The thin film provides greater coverage and low-cost protection.

Long-Term Protection

RP 585 is designed for long-term indoor and outdoor protection of steel.

Surface Preparation

The maximum performance for RP 585 can only be achieved when the metal surfaces, to be protected, are clean and dry. However, RP 585 is effective on lightly rusted surfaces.

Application

Agitate well to ensure uniform consistency prior to use. Continuous stirring or thinning are generally not required. If product thickens due to cold storage or loss of solvent during use, add only aliphatic mineral spirits and only if necessary to restore consistency.

Coverage

The theoretical coverage is approximately 900 sq. ft/gallon at the recommended dry film thickness of 1.0 mils (25 microns). Material losses during application will vary and must be considered when estimating job requirements.

SPECIFICATIONS

Flash Point	Approximately 135 F
Viscosity	Semi Fluid
Coverage	Approximately 900 square ft/gallon
Application	Spray, Dip, or Brush
Removal	Mineral Spirits

